

NOVA

Dependable Gas Analysis Solutions

317 SERIES

PORTABLE ANALYZER HYDROCARBONS



APPLICATIONS

For analysis of propane or gasoline vapors from a closed vessel or from a closed transfer line, such as with gas station vapor recovery applications.

FEATURES

- Rugged design that is easy to operate
- Fast warm-up and response
- Solid state infrared detector
- Calibrates on 100% propane; yields gasoline vapor measurement using a correction factor
- Digital readout meter with backlight
- Modular layout that is easy to maintain
- Rechargeable battery operation
- Built-in sample pump, filter and flow meter
- Suitcase style cabinet weatherproof when closed

OPTIONS

- 4-20mA recorder output
- Detachable/portable data logger
- Externally visible display
- High HC alarm with display indication

CALIBRATION

- Air for zero
- 100% propane for span



Standard suitcase enclosure (K)



Optional suitcase enclosure with external display (KX)

NOVA ANALYTICAL SYSTEMS

www.nova-gas.com

DESCRIPTION

The Nova 317 Series Portable Hydrocarbon Analyzer is designed for the measurement of propane or gasoline vapor (using a correction factor) from a closed vessel.

The built-in sampling pump draws in a sample through an external hose where it then passes through a filter, flow meter and infrared detector for measurement. The measurement results are then displayed on an easy-to-read digital meter with switchable backlight.

A built-in rechargeable battery has enough power for about 5 hours of continuous operation and the analyzer can be used while it is recharging. A red LED indicates when to recharge the analyzer and a green LED indicates that it is receiving recharging power. A recharger is included.

SPECIFICATIONS

Nova reserves the right to specification changes which may occur with advances in design without prior notice.

| Description | |
|------------------------------------|---|
| Method of Detection: | NDIR infra red detector (no moving parts) |
| Ranges Available: | 0-100.0% propane (other ranges available) |
| Resolution: | 0.1% propane |
| Accuracy and Repeatability: | ±2% of full scale |
| Drift: | Less than 2% of full scale per week |
| Response Time (T-90): | 10-15 seconds |
| Ambient Temperature Range: | 32-120°F (0-50°C) |
| Linearity: | ±2% of full scale |
| Size and Weight: | WP style - approx. 10" L x 7½" H x 6½" D @ 8 lbs (25.5 x 19 x 16.5 cm @ 3.6 kg) K style approx. 14" L x 6" H x 10½" D @ 8 lbs (35.5 x 15.2 x 26.6 cm @ 3.6 kg) |
| Power: | AC/DC operation. 115VAC 60Hz for recharging (other voltages available) |
| Output Options: | 4-20mA |
| Alarms: | High HC alarm (optional) |

UNIQUE APPLICATIONS

This instrument is not explosion-proof or 'intrinsically safe' design. User should observe all locally established precautionary measures when sampling potentially flammable or explosive spaces. All Nova analyzers are built using proven technologies and techniques. If this product does not suit your application, please contact Nova at 1-800-295-3771. In many cases, we are able to build an analyzer specific to your needs.



NOVA ANALYTICAL SYSTEMS
(A UNIT OF TENOVA GOODFELLOW INC.)

IN USA:
1925 Pine Avenue • Niagara Falls, NY • 14301
Tel: 1-800-295-3771 • 716.285.0418 • Fax: 716.282.2937
IN CANADA:
270 Sherman Avenue North • Hamilton, ON • L8L 6N5
Tel: 905.545.2003 • Fax: 905.545.4248
email: sales@nova-gas.com
websales@nova-gas.com



www.nova-gas.com